

THE STRINGER

Optional Configuration of the BRICKette™

Designed + Manufactured in America



#2106A-S5 or #2106C-S5 :: The BRICKette™ | Explosion Proof LED Work Light

December 2019



Multiple Mounting Options

Magnetic, Solid, or Slotted Handles- (See The BRICKette™ Datasheet for more info)



The STRINGER
(Optional Configuration)
Up to 5 Heads [in a Row]
1 Power Box



Product Features

- ▶ **Approved for:** Class I, Div 1 & 2, Group C & D
- ▶ **Approved for:** Class II, Div 1 & 2, Group E, F, & G
- ▶ **Approved for:** CSA Zones 1 & 2; Zones 20, 21, & 22
- ▶ **Conforms to:** UL Std's 153, 8750, 844;
- ▶ **Certified to:** CSA Std's C22.2#s 12, 25, 30, 137, 250.13
- ▶ **Suitable for Wet Location Use:** Type 6P
- ▶ **Certified:** Portable Luminary
- ▶ **Temperature Rating:** T-code: T5 (-25° to +40°C)
- ▶ **LED Color:** ~6000K, CRI >70
- ▶ **Rated with optics:** 26,000 lux at 1'
- ▶ **Rated with optics:** >2,500 lumens
- ▶ **Reflective Optic Beam Angle:** 60°
- ▶ **Light Head Power:** 21VDC, 800mA, LVLE
- ▶ **Weight:** 3.5 lbs (light head only) | 4.2-5.3 lbs (light head with handle)
- ▶ **Dimensions:** 6"L x 2.9"W x 2.3"H
- ▶ **Protection:** Polyurethane Bumper
- ▶ **Accessories:** Blast Shields, Dome Diffuser, Overspray Protection Bags
- ▶ **Variable Mounting Options:** Magnetic, Solid and Slotted Handles (High & Low Profiles, Short and Long Handles)

The STRINGER Proven Applications:

- Aircraft Manufacturing
- Paint Booths
- Ship Building & Repair
- Oil Refineries
- Chemical Processing

