TECHNOLOGY



Model 8100 - Explosion Proof LED Inspection/Work Light & Drop Light

February 2020



Hook Mouint (included w/ every STRIKER™ System)

> **Dome Diffuser** (included w/ every STRIKER™ System)



The STRIKER™ Short Handle Drop Light shown w/ Hook Mount & Dome Diffuser



Replaceable **Blast Lenses** (Box of 12)

The STRIKER®

C-Model - Short Handle **Explosion Proof Power Box Explosion Proof Plug** #8100-3C SH



Product Features

Class I, Div 1 & 2, Group C & D Approved for: Class II, Div 1 & 2, Group E, F, & G

CSA Zones 1 & 2; Zones 20, 21, & 22

Conforms to: UL Stds 153, 8750, 781, 844;

Certified to: CSA Stds C22.2#s 12. 25. 137

Suitable for: Wet Location Use

Certified: Portable Luminary (Portable Luminaire)

T-code: T5 (-40°C to +40°C); T4 (-40°C to +100°C) Temperature Rating:

LED Color: ~6000K. CRI >70

- 45,000 lux at 1' **Light Output:** - >2,100 lumens

Standard Optic: 25° refractive, collimated beam

- 21VDC, 800mA, LVLE (A & C Models) - 120 VAC, 3A (B Model) **Light Head Power:**

Weight:

3 lbs (light head only)~20lbs (light head & 100' cable

Short Handle (8.2"L x 3"D)Long Handle (13.5"L x 3"D) **Dimensions:**

- Machined solid blocks of 6061-T6 Aluminum **Body Material:**

- Polyurethane Bumpers

Accessories: Blast Lens, Dome Diffusers, Hanging Hook

Country of Origin: Designed & Manufactured in the USA













The STRIKER™ **B-Model** All-in-One - Long Handle **Ex-Proof Plug** #8100-3B

The STRIKER™ Long Handle









Western Technology, Inc. 3517 Arsenal Way Bremerton, WA 98312 Fax: (360) 917-0083

Toll Free: (800) 654-5483 Local: (360) 917-0080